



Solid Polymer Electrochemical Gas Sensing Technology

ES1-AG1-2000-01

All Gas Sensor
Datasheet

Easy Gas Sensor

ES1-AG1-2000 All Gas



Part Number

01-ES1-AG1-2000-01

Features

- ☞ Detects with high selectivity a wide variety of gases
- ☞ Long lifetime > 3 years
- ☞ No-poisoning
- ☞ Typical warm-up time in seconds
- ☞ Fast response time
- ☞ nA power consumption
- ☞ Linear output
- ☞ No zero line drift
- ☞ Better signal to noise ratio
- ☞ Wide temperature range of -40 °C to +55 °C
- ☞ Excellent sensitivity at low temperatures
- ☞ No leakage
- ☞ Small size
- ☞ RoHS compliant

Typical Applications

- ☞ Emission Monitoring
- ☞ Indoor Air Quality



Technical Specifications

Performance

Sensitivity	11 nA/ppm ± 4 nA/ppm
Zero Current	± 100 nA
Range	0 - 2000 ppm
Maximum Overload	5000 ppm
Resolution (16Bit ADC)	0.1 ppm
Response Time	T ₅₀ < 10 s, T ₉₀ < 30 s
Repeatability	1 %
Linearity	Linear

Environment

Operating Temperature Range	-40 °C to +55 °C
Operating Humidity Range	15-95% RH non-condensing
Operating Pressure Range	800 to 1200 hPa
Storage Temperature	0 °C to 20 °C (Optimum temp. 4 °C to 6 °C)

Operation

Operating Principle	Amperometric, 3-electrode
Bias Voltage	0 mV
Recommended Load Resistor	100 Ω
Warm-Up Time	< 60 s

Lifetime


Long-Term Drift *	< 5 %/year
Expected Lifetime	> 3 years
Zero Drift in Clean Air	< 1 ppm
Storage Life	12 months
Warranty	12 months

*Note: Long-Term Drift may vary depending on storage conditions and usage.

Housing

Housing Material	PPO
Weight	< 0.7 g

» Dimensions (Unit: mm)



» Cross Sensitivity

The "Test Concentration" was used to test the sensor. The "Sensor Reading" applies to the amount of the "Calculated Test Concentration".

Gas	Formula	Test Concentration	Calculated Test Concentration	Sensor Reading
Ethanol (Alcohols)	C_2H_6O	500 ppm	1 ppm	0.48 ppm
Ammonia	NH_3	20 ppm	1 ppm	0 ppm
Arsine	AsH_3	10 ppm	1 ppm	4 ppm
Benzene	C_6H_6	-	1 ppm	NE***
Bromine	Br_2	-	1 ppm	NRE**
Methane	CH_4	-	1% vol.	0% vol.
Carbon Dioxide	CO_2	-	10% vol.	0% vol.
Carbon Monoxide	CO	100 ppm	100 ppm	100 ppm
Chlorine	Cl_2	-	1 ppm	NRE**
Chlorine Dioxide	ClO_2	-	1 ppm	NRE**
Diborane	B_2H_6	-	1 ppm	PRE*
Ethylene	C_2H_4	10 ppm	1 ppm	0 ppm
ETO Ethylene Oxide	C_2H_4O	10 ppm	1 ppm	0 ppm
Hydrazine	N_2H_4	-	1 ppm	PRE*
Hydrogen Chloride	HCl	-	1 ppm	NRE**
Hydrogen Cyanide	HCN	10 ppm	1 ppm	0.75 ppm
Hydrogen Fluoride	HF	-	1 ppm	NRE**
Iodine	I_2	-	1 ppm	NRE**
Nitric Oxide	NO	-	5 ppm	PRE*
Phosphine	PH_3	5 ppm	1 ppm	3.9 ppm
Silane	SiH_4	-	1 ppm	PRE*
Isopropanol	C_3H_8O	-	1 ppm	PRE*
Formaldehyde	$HCHO$	-	1 ppm	PRE*
Dimethyl Disulfide	$C_2H_6S_2$	-	1 ppm	PRE*
Methanol	CH_3OH	-	1 ppm	PRE*
Gasoline Volatilization	-	-	1 ppm	PRE*
Dining Lampblack	-	-	1 ppm	PRE*
Trimethylamine	C_3H_9N	-	1 ppm	PRE*
Fluorine	F_2	-	1 ppm	NRE**

Gas	Formula	Test Concentration	Calculated Test Concentration	Sensor Reading
Hydrogen Bromide	HBr	-	1 ppm	NRE**
Dichlormethane	CH ₂ Cl ₂	-	1 ppm	NRE**
Tetrahydrothiophene	C ₄ H ₈ S	-	1 ppm	PRE*
Hydrocarbons (unsaturated)	-	-	1 ppm	NE***
Germane	GeH ₄	-	1 ppm	PRE*

* Positive Reading Expected


** Negative Reading Expected

*** Not Expected

Note:

- 1) The above interference factors may vary due to different sensors and service life, please refer to the actual test results.
- 2) This table is not complete for all cross gases. Please contact us for other gases.
- 3) The above parameters are the test results at a temperature of 25 °C, a relative humidity of 50% RH and a normal pressure environment. The performance of the sensor varies under different environmental conditions. If you have any questions, please contact us.
- 4) The above cross interferences are represented by a low concentration of the gas.

» Temperature Curve



Disclaimer

The EC Sense performance data stated above is based on data obtained under test conditions using the EC Sense gas distribution system and AQS test software. In the interest of continuous product improvement, EC Sense reserves the right to change design features and specifications without notice. We are not responsible for any loss, injury or damage caused by this. EC Sense assumes no responsibility for any indirect loss, injury or damage resulting from the use of this document, the information contained therein or any omissions or errors herein. This document does not constitute an offer to sell. The data it contains are for informational purposes only and cannot be considered a guarantee. Any use of the given data must be evaluated and determined by the user to comply with federal, state and local laws and regulations. All specifications outlined are subject to change without notice.

 **Warning**

EC Sense sensors are designed for use in a variety of environmental conditions. However, due to the principles and characteristics of solid polymer electrochemical sensors and to ensure normal use, users must strictly follow this article during storage, assembly and operation of the module. Avoid cleaning the sensors with alcohol, acetone or other strong solvents. General-purpose PCB circuit board application methods and illegal applications or violation of the application will not be covered by the warranty. Although our products are highly reliable, we recommend checking the module's response to the target gas prior to utilization to ensure on-site use. At the end of the product's service life, please do not discard any electronics in the domestic waste, instead follow the local governments electronic waste recycling regulations for disposal.



Business Centre
Europe and the rest of the world

EC Sense GmbH
Wangener Weg 3
82069 Hohenschäftlarn, Germany
Tel: +49(0)8178-99992-10 Fax: +49(0)8178-99992-11
Email: office@ecsense.com
www.ecsense.com

Business Centre
Asia

Ningbo AQSystems Technology Co., Ltd.
6 Building, Zhong Wu Technology Park No.228,
Jin Gu North Road, Yinzhou District NingBo,
Zhejiang Province, P.R. China Post Code: 315100
Tel: +86(0)574 88097236, 88096372
Email: info@aqsystems.cn
www.ecsense.cn