



4-20mA
Smart Oxygen Sensor Module
TB420-ES1-O₂
Datasheet

» Overview

Easy solution for gas detection instruments and systems


The TB420 Gas Sensor Module is an intelligent two wire 4-20mA digital gas sensor module from EC Sense, which utilizes a smart microprocess with high-reliability solid polymer electrochemical gas sensing technology and intelligent algorithm calculation. The TB420 is designed to comply with the relevant standards for gas safety monitoring in the industrial application.

The TB420 Gas Sensor Module is for indoor and outdoor environments. It detects gas, and easily receives all of the data simultaneously. The changing state of gas is closely related to temperature and humidity for which this combination of EC Sense's Gas Sensor Module offers a professional solution.

The intelligent Gas Sensor Module provides a self-test which evaluates the sensor performance without a gas measurement. It is therefore an excellent solution for smart home and IoT applications. The data is put out through the output signal, which makes it easy and convenient to identify the right time to perform maintenance and replacement.

Each TB420 Sensor Module has been professionally calibrated with the gas. It can be instantly used without prior warm-up time and the calibration information is stored in the flash chip. There is a calibration software from EC Sense in case a recalibration should be performed or the 4-20mA output signal is to be corrected.

The TB420 Gas Sensor Module effectively shortens gas instrument development time, reduces cost and risk in new product development, saves production time, avoids complex gas calibration steps and ensures high reliability and accuracy. The standard 4-20mA two-wire module facilitates quick instrument and system setup or connection to display, DCS, PLC and other systems.



» Key Features

- ☞ 4-20mA standard two-wire output, 24V DC. power supply
- ☞ Detects single gas
- ☞ Pre-calibration with sensor performance and life-testing output
- ☞ Fast signal stability time at power on
- ☞ Suitable for indoor and outdoor environments, sensor can work in -40 to 55 °C
- ☞ Response time is fast and has a stable zero point without drift, anti-electromagnetic interference ability
- ☞ Long lifetime gas sensor, anti-poisoning
- ☞ Integrated safety protection enables use in potentially explosive environments
- ☞ Electronic circuit boards have a dust and corrosion resistant coating
- ☞ Small size
- ☞ RoHS approved

» Applications


- ☞ Industrial gas safety monitoring
- ☞ Industrial process gas monitoring
- ☞ Leakage safety monitoring of oxygen, nitrogen or other inert gases
- ☞ Oxygen leakage monitoring in the field of gas manufacturing
- ☞ Biogas monitoring
- ☞ Warehouse logistics environment monitoring
- ☞ Transformer failure and power chamber environment monitoring
- ☞ Medical & Health Care



» Principle


TB420 Sensor Module is a durable product. It converts the original small current signals of the gas sensors into standard 4-20mA outputs through a digital circuit. It is also possible to convert an external resistor to a 40-200 mV voltage output.

The Sensor Module uses the Solid Polymer Electrochemical Sensing Technology. It employs a three-electrode arrangement - the working, the counter and the reference electrodes - in which concentration measurements can be performed continuously and the sensor operates at a fixed potential. The gas of interest (target gas) diffuses through a diffusion barrier, like a capillary, into the cell to the working electrode, where an electrochemical reaction takes place. There are oxidation and reduction reactions. The current flowing through the cell is direct proportional to the concentration of the target gas. A reference electrode keeps the potential constant together with a potentiostat.




» Mechanical Drawing


TB420-ES1 Gas Sensor Module



Product Schematic




Side View




Top View

4-20mA Connector



Product Schematic



Side View

» Technology Specifications

Gas Sensor Specifications

| | |
|-------------------|--|
| Principle | Solid Polymer Electrochemical Sensing Technology |
| Accuracy | ± 5 % Full scale |
| Repeatability | < 2% |
| Linearity | Linear |
| Long-Term Drift | < 1% / month |
| Expected Lifetime | > 3 years |

Electrical Specifications

| | |
|-------------------------|--|
| Output Signal | 4-20mA two-wires |
| Fault Output | 3.5mA Fault Signal: Sensor signal weak |
| | 3mA Fault Signal: Sensor failure or sensor disconnection |
| Supply Voltage | 9 to 24V DC, 24V DC recommended |
| Supply Current | 3 to 22mA |
| Power Consumption | < 0.6W |
| Maximum Loop Resistance | < 500R @ 24V DC |
| Protection | Reverse polarity protection |

Environment Specifications

| | |
|-----------------------|-----------------------------------|
| Operating Temperature | Sensor can work from -40 to +55°C |
| Operating Humidity | 15-95% RH. non-condensing |
| Operating Pressure | Atmospheric pressure ± 10% |
| Storage Temperature | 0 to 20°C |

Mechanical Specifications

| | |
|-------------------------------|--------------------------|
| Size (Including Gas Sensor) | 45 x 35 x 11.9mm |
| Size (Without Gas Sensor) | 45 x 35 x 11.9mm |
| Weight (Including Gas Sensor) | 7.8g |
| Weight (Without Gas Sensor) | 7.1g |
| Warranty | 12 months |
| Package | ESDBAG Size: 120 x 150mm |

» Order Information

| Product | Gas Formula | Partnumber | Range | Resolution | Response Time |
|----------------------------|----------------|-------------------------------------|-----------|------------|---------------|
| Smart Oxygen Sensor Module | O ₂ | 04-TB420-ES1-O ₂ -25%-01 | 0-25%vol. | 0.01%vol. | T90 < 30s |

Disclaimer

The EC Sense performance data stated above is based on data obtained under test conditions using the EC Sense gas distribution system and AQS test software. In the interest of continuous product improvement, EC Sense reserves the right to change design features and specifications without notice. We are not responsible for any loss, injury or damage caused by this. EC Sense assumes no responsibility for any indirect loss, injury or damage resulting from the use of this document, the information contained therein or any omissions or errors herein. This document does not constitute an offer to sell. The data it contains are for informational purposes only and cannot be considered a guarantee. Any use of the given data must be evaluated and determined by the user to comply with federal, state and local laws and regulations. All specifications outlined are subject to change without notice.

Warning

EC Sense sensors are designed for use in a variety of environmental conditions. However, due to the principles and characteristics of solid polymer electrochemical sensors and to ensure normal use, users must strictly follow this article during storage, assembly and operation of the module. General-purpose PCB circuit board application methods and illegal applications / violation of the application will not be covered by the warranty. Although our products are highly reliable, we recommend checking the module's response to the target gas prior to utilization to ensure on-site use. At the end of the products service life, please do not discard any electronics in the domestic waste, instead follow the local governments electronic waste recycling regulations for disposal.



**Business Centre
Europe and the Rest of the World**

EC Sense GmbH
Wangener Weg 3
82069 Hohenschäftlarn, Germany
Tel: +49(0)8178-99992-10 Fax: +49(0)8178-99992-11
Email: office@ecsense.com
www.ecsense.com www.ecnose.de

**Business Centre
Asia**

Ningbo AQSystems Technology Co., Ltd.
F4-17 Building, Zhong Wu Technology Park No.228,
Jin Gu Bei Road, Yinzhou District NingBo,
Zhejiang Province, P.R. China Post Code: 315100
Tel: +86(0)574 88097236, 88096372
Email: info@aqsystems.cn
www.ecsense.cn, www.ecnose.de