



Smart Gas Sensor Device

Stox Series

Datasheet

» Overview

Easy solution for gas detection












The Stox Smart Gas Sensor Device is an intelligent sensor device from EC Sense, which has a 4-20 mA two-wire and a RS485 Modbus RTU output signal. It uses an intelligent microprocessor with high-reliability solid polymer electrochemical gas sensor technology and intelligent algorithm calculation. The Stox Device is a smart solution for industrial safety applications, combining temperature and humidity in one sensing device.

The Smart Gas Sensor Device provides a self-test, which evaluates the sensor performance without a gas measurement. Therefore, it is the excellent solution for smart home and IoT applications. The data is put out through the the output signal or RS485 transmission command, which makes it easy and convenient to identify the right time to perform maintenance and replacement.





Each Stox Sensor Device has been professionally calibrated with the gas. It can be instantly used without prior warm-up time and the calibration information is stored in the flash chip. There is a calibration software from EC Sense in case a recalibration should be performed with the RS485 output or the 4-20 mA output signal should be corrected.

The Stox Gas Sensor Device has a standard 4-20 mA two-wire or RS485 Modbus RTU output signal that allows for quick device and system setup or connection to a display, DCS, PLC and other systems.

» Key Features

-  4-20 mA standard two-wire and RS485 Modbus-RTU output, 24V DC. power supply
-  Detects single gas + temperature and humidity at the same time
-  With calibration, sensor performance and life-testing output
-  Fast signal stability time at power on
-  Suitable for indoor and outdoor environments, sensor can work in -40 °C to +55 °C
-  Response time is fast and has a stable zero point without drift, anti-electromagnetic interference ability
-  Long lifetime, anti-poisoning
-  Integrated safety protection enables use in potentially explosive environments
-  Electronic circuit boards have a dust and corrosion resistant coating
-  Small size
-  RoHS approved

» Applications


-  Industrial Gas Safety Monitoring
-  Industrial Process Gas Monitoring
-  Air Exchange System and Air Purifier
-  Food Storage Insecticides Monitoring
-  Wastewater Treatment, Garbage Disposal, Biogas Safety Monitoring
-  Medical & Health Care
-  Semiconductor Gas Purification Monitoring
-  Transformer Failure and Power Chamber Environment Monitoring
-  Warehouse Logistics Environment Monitoring



» Principle


The Stox Sensor Device is a durable product. It converts the original small current signals of the gas sensors into a standard 4-20 mA or RS485 Modbus-RTU output through a digital circuit.

The Sensor Device uses the Solid Polymer Electrochemical Sensing Technology. It employs a three-electrode arrangement- the working, the counter and the reference electrodes- in which concentration measurements can be performed continuously and the sensor operates at a fixed potential. The gas of interest (target gas) diffuses through a diffusion barrier, like a capillary, into the cell to the working electrode, where an electrochemical reaction takes place. Oxidation and reduction reactions are happening simultaneously. The current flowing through the cell is direct proportional to the concentration of the target gas. A reference electrode keeps the potential constant together with a potentiostat.



» Mechanical Drawing (Unit: mm)

Stox Series Gas Sensor Device Mechanical Drawing



» Technology Specifications

Gas Sensor Specifications

Detection Gas	Please choose from "Order Information"
Range	Please choose from "Order Information"
Resolution	Please see the "Order Information"
Response Time	Please see the "Order Information"
Principle	Solid Polymer Electrochemical Sensing Technology / Liquid Electrochemical Sensing Technolog
Accuracy	± 5% (Mesurement value)
Repeatability	< 2 %
Linearity	Linear
Long-Term Drift	< 5%/year
Expected Lifetime	> 3 years

Temperature & Relative Humidity Sensor Specification

Parameter	Range	Resolution	Accuracy	Repeatability	Response Time	Long-Term Drift
Temperature	-40 °C to +85 °C	0.01 °C	± 0.2 °C	0.1 °C	< 5s to 30s @ t63%	< 0.02°C /year
Humidity	0-100% RH	0.01% RH	± 2% RH	0.1% RH	8s @ t63%	< 0.25% RH/year

Electrical Specifications

Optional Output Signal	4-20 mA two-wires (Only gas sensor ouput, without temperature and humidity) Or RS485 Modbus-RTU (Gas with temperature and humidity sensor signal output)
Fault Output	3.5 mA Fault Signal: Sensor signal weak 3 mA Fault Signal: Sensor failure or sensor disconnected RS485 Modbus-RTU output with sensor life and performance detection and early sensor failure warning
Supply Voltage	12 to 24V DC
Supply Current	3 to 22 mA
Power Consumption	< 0.6 W
Maximum Loop Resistance	< 500R @ 24V DC

Environment Specifications

Operating Temperature	Sensor can work from -40 °C to +55 °C
Operating Humidity	15-95% RH non-condensing
Operating Pressure	Atmospheric pressure ± 10 %
Storage Temperature	0 °C to 20 °C

Mechanical Specifications

Size	39 x 130 mm
Weight	135 g
Power Cable length	1 m
Warranty	12 months
Package Size	185 x 150 x 108 mm

» Order Information

Product	Gas Formula	Partnumber	Range	Resolution	Response Time
Smart Arsine Sensor Device	AsH ₃	05-Stox-AsH ₃ -1-01	0-1 ppm	0.001 ppm	< 3 s (T90 < 80 s)
Smart Diborane Sensor Device	B ₂ H ₆	05-Stox-B ₂ H ₆ -1-01	0-1 ppm	0.001 ppm	< 3 s (T90 < 80 s)
Smart Bromine Sensor Device	Br ₂	05-Stox-Br ₂ -1-01	0-1 ppm	0.001 ppm	T90 < 60 s
Smart Methyl Mercaptan Sensor Device	CH ₄ S	05-Stox-CH ₄ S-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 80 s)
		05-Stox-CH ₄ S-100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 80 s)
		05-Stox-CH ₄ S-5000-01	0-5000 ppm	0.1 ppm	< 3 s (T90 < 80 s)
Smart Chlorine Sensor Device	Cl ₂	05-Stox-Cl ₂ -5-01	0-5 ppm	0.001 ppm	T90 < 60 s
		05-Stox-Cl ₂ -50-01	0-50 ppm	0.01 ppm	T90 < 60 s
		05-Stox-Cl ₂ -100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
Smart Chlorine Sensor Device	ClO ₂	05-Stox-ClO ₂ -5-01	0-5 ppm	0.001 ppm	T90 < 60 s
Smart Carbon Monoxide Sensor Device	CO	05-Stox-CO-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 80 s)
		05-Stox-CO-100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-CO-1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-CO-2%-01	0-2% vol.	0.001% vol.	< 3 s (T90 < 30 s)
Smart Ethylene Oxide Sensor Device	ETO (C ₂ H ₄ O)	05-Stox-ETO-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-ETO-200-01	0-200 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-ETO-1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
Smart Fluorine Sensor Device	F ₂	05-Stox-F ₂ -5-01	0-5 ppm	0.001 ppm	T90 < 60 s
Smart Germane Sensor Device	GeH ₄	05-Stox-GeH ₄ -5-01	0-5 ppm	0.01 ppm	< 3 s (T90 < 80 s)
Smart Hydrogen Sensor Device	H ₂	05-Stox-H ₂ -1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ -5000-01	0-5000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ -5%-01	0-5% vol.	0.001% vol.	< 35 s (T90 < 90 s)
Smart Sulfur Hydrogen Sensor Device	H ₂ S	05-Stox-H ₂ S-5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ S-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ S-100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ S-1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-H ₂ S-5000-01	0-5000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-HCHO-5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 80 s)
Smart Formaldehyde Sensor Device	HCHO	05-Stox-HCHO-100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 60 s)
Smart Hydrogen Chloride Sensor Device	HCl	05-Stox-HCl-30-01	0-30 ppm	0.001 ppm	T90 < 60 s
Smart Hydrogen Cyanide Sensor Device	HCN	05-Stox-HCN-50-01	0-50 ppm	0.01 ppm	< 3 s (T90 < 30 s)
Smart Hydrogen Fluoride Sensor Device	HF	05-Stox-HF-10-01	0-10 ppm	0.001 ppm	T90 < 60 s
Smart Ammonia Sensor Device (Long lifetime)	NH ₃	05-Stox-NH ₃ -10-LL-01	0-10 ppm	0.001 ppm	< 3 s, no T90
		05-Stox-NH ₃ -100-LL-01	0-100 ppm	0.01 ppm	< 3 s, no T90
Smart Ammonia Sensor Device (Fast response)	NH ₃	05-Stox-NH ₃ -100-FR-01	0-100 ppm	0.01 ppm	T90 < 60 s
		05-Stox-NH ₃ -500-FR-01	0-500 ppm	0.1 ppm	T90 < 60 s
		05-Stox-NH ₃ -1000-FR-01	0-1000 ppm	0.1 ppm	T90 < 60 s

» Order Information

Product	Gas Formula	Partnumber	Range	Resolution	Response Time
Smart Nitrogen Dioxide Sensor Device	NO ₂	05-Stox-NO ₂ -5-02	0-5 ppm	0.001 ppm	< 3 s (T90 < 80 s)
		05-Stox-NO ₂ -50-01	0-50 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-NO ₂ -100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-NO ₂ -1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-NO ₂ -2000-01	0-2000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
Smart Oxygen Sensor Device	O ₂	05-Stox-O ₂ -25%-01	0-25% vol	0.01% vol.	< 3 s (T90 < 30 s)
Smart Ozone Sensor Device	O ₃	05-Stox-O ₃ -5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 80 s)
		05-Stox-O ₃ -50-01	0-50 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-O ₃ -100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
Smart Phosphine Sensor Device	PH ₃	05-Stox-PH ₃ -5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 80 s)
		05-Stox-PH ₃ -20-01	0-20 ppm	0.01 ppm	< 3 s (T90 < 80 s)
		05-Stox-PH ₃ -100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 80 s)
		05-Stox-PH ₃ -2000-01	0-2000 ppm	0.1 ppm	< 3 s (T90 < 80 s)
Smart Silane Sensor Device	SiH ₄	05-Stox-SiH ₄ -10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 80 s)
Smart Odor Sensor Device	SMELL	05-Stox-SMELL-5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-SMELL-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-SMELL-200-01	0-200 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-SMELL-500-01	0-500 ppm	0.1 ppm	< 3 s (T90 < 30 s)
Smart Sulfur Dioxide Sensor Device	SO ₂	05-Stox-SO ₂ -5-01	0-5 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-SO ₂ -50-01	0-50 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-SO ₂ -100-01	0-100 ppm	0.01 ppm	< 3 s (T90 < 30 s)
		05-Stox-SO ₂ -1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-SO ₂ -2000-01	0-2000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
Smart Organic Volatiles Sensor Device	TVOC	05-Stox-TVOC-10-01	0-10 ppm	0.001 ppm	< 3 s (T90 < 30 s)
		05-Stox-TVOC-200-01	0-200 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-TVOC-1000-01	0-1000 ppm	0.1 ppm	< 3 s (T90 < 30 s)
		05-Stox-TVOC-2000-01	0-2000 ppm	0.1 ppm	< 3 s (T90 < 30 s)

Disclaimer

The EC Sense performance data stated above is based on data obtained under test conditions using the EC Sense gas distribution system and AQS test software. In the interest of continuous product improvement, EC Sense reserves the right to change design features and specifications without notice. We are not responsible for any loss, injury or damage caused by this. EC Sense assumes no responsibility for any indirect loss, injury or damage resulting from the use of this document, the information contained therein or any omissions or errors herein. This document does not constitute an offer to sell. The data it contains are for informational purposes only and cannot be considered a guarantee. Any use of the given data must be evaluated and determined by the user to comply with federal, state and local laws and regulations. All specifications outlined are subject to change without notice.

Warning

EC Sense devices are designed for use in a variety of environmental conditions. However, due to the principles and characteristics of sensors and to ensure normal use, users must strictly follow this article during storage, assembly and operation of the device. Although our products are highly reliable, we recommend checking the device's response to the target gas prior to utilization to ensure on-site use. At the end of the products service life, please do not discard any electronics in the domestic waste, instead follow the local governments electronic waste recycling regulations for disposal.



**Business Centre
Europe and the Rest of the World**

EC Sense GmbH
Wangener Weg 3
82069 Hohenschäftlarn, Germany
Tel: +49(0)8178-99992-10 Fax: +49(0)8178-99992-11
Email: office@ecsense.com
www.ecsense.com

**Business Centre
Asia**

Ningbo AQSystems Technology Co., Ltd.
6 Building, Zhong Wu Technology Park No.228,
Jin Gu North Road, Yinzhou District NingBo,
Zhejiang Province, P.R. China Post Code: 315100
Tel: +86(0)574 88097236, 88096372
Email: info@aq-s-de.com
www.ecsense.cn